

BACPRINT DUAL



The BACPRINT DUAL is a washing and developing tank used in the screen printing industry. The BACPRINT DUAL is equipped with pneumatic valve to make the separation from water and solvent. The BACPRINT DUAL is equipped with 2 pneumatic pumps that never mixing dirty solvent with clean solvent.

www.acosgraf.com





www.acosgraf.com








Color system identification from solvents clean/dirty

Bottom rail with inclination and leveling adjustment VIndividual pressure gauge from pressure apply to each pump







Full automatic water treatment systems available

Decanting solvents with 3 levels and easy cleaning

Acrylic transparent door to protect operator from water splashing as option

PRODUCT DESCRIPTION

Modular construction in stainless steel;

Solvent decantung with 3 levels;

2 pneumatic pumps for non-contamination of clean solvents;

Screen rail horzonatl holder with possibility of inclination adjustment;

Prepared for application of fan for toxic vapors aspiration;

Deposit of clean solvents;

Solvent pumps with pressure gauge indicator;

Possibility of having 2 independent circuits of effluents: water and solvents without cross contamination;

Color system brush for a better identification of clean / dirty solvents;

Solvent deposits with level indication;

BACPRINT DUAL	Uni	BACDUAL 0710	BACDUAL 1013	BACDUAL 1316	BACDUAL 1518
Max screen size	Cm	70×100	100x130	130x160	150x180
External deepth	Cm	95	95	95	95
External width	Cm	116	146	176	195
External height	Cm	195	207	237	255
Air pressure	BAR	6	6	6	6
Weight	Kg	120	160	180	
Voltage	V	230	230	230	230

Note: As caracteristicas podem ser alteradas sem aviso prévio